

Technical specifications

Bridge Banners

When print data is delivered

Format (w × h)	Please use the size indicated in the offer/order confirmation. In your interest, relevant information should not be printed on the border area (5 cm).
Print file format	Format + bleed
File type	PDF-X4
Bleed	10 mm circumferential
Resolution	300 dpi (not scaled, moved to the format of the print file)
Color mode	CMYK
Fonts	Conversion into character paths or delivery
Color profile	ISOcoated_v2_300_eci oder ISOcoated_v2_eci (available under: http://www.eci.org/de/downloads)
Print data delivery	Up to 20 days before the start
Data transmission	Via eMail or OwnCloud - we will send you the specifications
Color proof	A proof of UGRA-FOGRA standard with measurable media wedge will be provided by you or upon request, charged by DIE DRAUSSENWERBER

Upon delivery of the banner

Format (w × h)	Please use the size indicated in the offer/order confirmation.
Material	PVC fabric: tear-resistant, UV- and weather-resistant, colourfast, opaque and eyeleted
Printing documents	If you do not use DIE DRAUSSENWERBER for production, please contact the respective printing company for exact specifications of the print data.
Delivery	Free delivery, in suitable transport packaging, at the latest 20 days before start of posting
Eyelets	At regular intervals of 50 cm in the hemmed i.e. material-reinforced edge area of the banner
Delivery address	DIE DRAUSSENWERBER GmbH // An der Spreeschanze 6 // 13599 Berlin // Mo-Fr 6.30-15.30 Uhr

Other information DIE DRAUSSENWERBER take over the assembly of the advertising media.
The fastening materials are provided by DIE DRAUSSENWERBER.

Example Bridge Banners

